

SPEED POST

प्रसार भारती
(भारत का लोक सेवा प्रसारक)
दूरदर्शन केन्द्र : झालाना डूंगरी, जयपुर-302 004

संख्या/दूदक/जय/1(32)2013-14-E/

दिनांक : 21-04-2014

पत्र पीछे लिखे अनुसार

विषय:- 10x2 ANALOG AUDIO/VIDEO SWITCHER की खरीद हेतु निविदा ।

महोदय,

कृपया संलग्न प्रपत्र में उल्लेखित तकनीकी सामान के लिए अपना भाव (कोटेशन) भेजें। कोटेशन मुहरबंद लिफाफे में अधोहस्ताक्षरकर्ता के पास दिनांक 15.05.2014 को दोपहर 12 बजे तक पहुँच जाना चाहिए। लिफाफे पर निम्नलिखित विवरण अवश्य लिखें। अपनी दरें प्रति नग के हिसाब से संलग्न प्रपत्र (ANNEXURE) में दें।

- 1 जिस कार्य के लिए कोटेशन भेजा गया है।
- 2 पत्र का सन्दर्भ।
- 3 कोटेशन खोलने की तारीख।

कोटेशन अधोहस्ताक्षरकर्ता के कार्यालय में दिनांक 15.05.2014 को दोपहर बाद तीन बजे, टेंडर भेजने वाले या उनके एजेंट की उपस्थिति में, यदि वे आते हैं तो, खोला जायेगा। भेजा गया कोटेशन स्वीकृति के लिए उसके खोलने की तारीख से 180 दिनों तक खुला रहेगा। किसी भी निविदा को बिना कारण बताये निरस्त करने का अधिकार उपमहानिदेशक (अभियान्त्रिकी) को सुरक्षित रहेगा।

भवदीय

(पी0 के0 कुलश्रेष्ठ)

सहायक अभियन्ता

कृते: उपमहानिदेशक (अभियान्त्रिकी)


संलग्न: प्रपत्र 2 पेज

प्रतिलिपि:- सूचना पट्ट ।

o/c

Technical Specifications for purchase of 10X2 Analog Audio/Video (Married) Router

Technical details for Main Frame Make-Internationally accepted such as Navion, Network, Shasta, Kramer, Ross, Siera etc.	Qty	Rate In Rs	Taxes	Total amount in Rs
Video Specifications:- Type of I/P & O/P Connectors BNC Type of I/P & O/P Analog Video Video Standard PAL BG Input Impedance 75 Ohm Input return loss >45dB DC to 6 MHz Output return loss >45dB DC to 6 MHz Input Level 1 V p-p Nominal Output Level 1 V p-p Nominal Frequency response ± 0.5 dB DC to 6 MHz Differential Gain <0.1%, Differential Phase <0.1% Tilt <0.1%, Noise Better than 60dB Output to Output Isolation > 90dB at Sub Carrier Frequency Reference Input Analog Black Burst No. of Video Inputs 10, No. of Video Outputs 02	02Sets			
Audio Specifications:- Type of I/P & O/P Analog Audio Connector type XLR or DB 25 Input Impedance > 20 Kohms Output Impedance < 50 Ohms Frequency response 20 Hz to 20 KHz ± 0.5 dB THDN <0.005%, SNR Better than 90dB Cross Talk >85dB, Input CMRR > 75dB No. of Audio Inputs 10 (Stereo) No. of Audio Outputs 02 (Stereo)				
General Data:- Serial Control Port 01 Serial Port Ethernet connectivity 10/100 Base T Operating Temperature 0 to 40°C Relative Humidity 0 to 90% non condensing AC Input 90 to 250V AC, 50Hz Mounting 19" Rack Mounting				
X-Y Control Panel suitable for above Audio/Video Router with LCD display	02			
Cables	02Sets As per requirement			
Audio Breakout Panel suitable for above Audio/Video Router	02			
Operation and Maintenance Manuals & operating software with media & permanent licence.	02Sets			



(P K Kulshrestha)
Assistant Engineer
For Dy. Director General (E)

Terms and conditions:-

- 1 No advance payment is admissible.
- 2 The Tenderer should attach the copy of TIN certificate with the quotation.
- 3 The Tenderer should attach the list of supply orders for such items supplied to AIR/Doordarshan.
- 4 All of above required items should be of broadcast standard.
- 5 The quantity mentioned in the annexure is tentative and can be increased or decreased with the approval of competent Authority.
- 6 Only Broadcast/professional quality make/models will be accepted and Commercial/Consumer quality items will be rejected without any clarification.
- 7 The TIN No. of the Firm should be clearly mentioned on the quotation.



(P K Kulshrestha)
Assistant Engineer
For DDG (E)